



ISOLMANT ISOLDRUM NASTRO ALLUMINATO

UNDERSCREED INSULATION - ACCESSORY

WHAT IS ISOLMANT ISOLDRUM NASTRO ALLUMINATO

5 cm height HD aluminate adhesive strip. This product is specially conceived to seal Isolmant Isoldrum sheets without overlapping fabric, in particular Isoldrum Top and Isoldrum LVT Plus. Sheets Thickness < 1 mm.

SPECIFIC APPLICATIONS

Isolmant Isoldrum Nastro Alluminato is specifically designed for sealing the sheets of Isolmant Isoldrum without adhesive overlapping fabric to ensure the continuity of the sheets installed, a perfect seal against vapour and the continuity of the reflective surface.

ADVANTAGES

- High tear resistance.
- Very low thickness.
- Vapour barrie.
- Continuity of the reflective surface is ensured.
- Inalterable over time.

ISOLMANT ISOLDRUM NASTRO ALLUMINATO TECHNICAL SPECIFICATIONS

NOMINAL THICKNESS:	< 1 mm
VAPOUR RESISTANCE	$S_d > 150 \text{ m}$
CE MARKING:	Harmonised standards for CE marking are NOT currently available for acoustic insulation products. This means that Isolmant products are currently NOT subject to CE marking, nor to the drawing up of a PDO (declaration of performance) or DDP (declaration of performance). All Isolmant products are placed on the market in compliance with the regulations in force in the country of destination and with the necessary certifications to guarantee their use in dedicated applications.
SIZE:	Rolls of 5 cm x 50 m linear
PACKAGE:	36-Roll paper boxes (1800 m HXL)

ITEM SPECIFICATIONS

Nastro adesivo in PET alluminato to seal Isolmant IsolDrum, in particular Isolmant IsolDrum TOP, Isolmant IsolDrum LVT Plus. H 5 cm.
Nominal thickness < 1 mm.

ISOLMANT ISOLDRUM NASTRO ALLUMINATO INSTALLATION



1

Installing Isolmant IsolDrum Nastro Alluminato. Isolmant IsolDrum underlay sheets must form a uniform and continuous layer to ensure the correct functioning of the system. It is therefore necessary (especially if the sheets do not have an adhesive overlapping fabric and if the continuity of the vapour barrier is required) to seal them using Isolmant IsolDrum Nastro Alluminato, cutting it to size as needed with a normal construction site cutter.

WARNINGS:

*This data sheet does not constitute a specification and, if it consists of several pages, please ensure that you have consulted the complete document. Although these instructions are the result of our best expertise they are indicative. The user should establish whether the product is suitable for its intended application. The user will be also in charge of all the responsibility for the use of the product itself.

**The sound insulation values given in this technical data sheet are the result of laboratory tests or tests carried out on site: they cannot be considered a predictive value for every situation that may occur on site. Acoustic performance is closely linked to the specific conditions of each site.

***Caution: do not expose the product to direct sunlight.

isolmant



Via dell'Industria 12, Località Francolino 20074 Carpiano (Mi) Tel. +39 02 9885701 Fax +39 02 98855702
clienti@isolmant.it - www.isolmant.it - www.sistemapavimento.it - www.isolmant4you.it

Isolmant is a TECNASFALTI srl's registered trademark - © TECNASFALTI - All rights reserved - Copying, even partially, is forbidden - In force since November 2020 - This document supersedes and replaces all previous versions.