



# ISOLMANT TELAIO PORTE

## UNDERSCREED INSULATION - ACCESSORY

### ACCESSORIES FOR UNDERFLOORING ACOUSTIC INSULATION TO USE ON FALSE FRAMES

#### WHAT IS ISOLMANT TELAIO PORTE?

Special accessories in pre-shaped and adhesive polyethylene for application in correspondence of false frames.

#### SPECIFIC APPLICATIONS

Isolmant Tealio Porte is specific for floating screeds as provided by UNI 11516:2013 standards with any type of slab. This product easily ensures the continuity of the flanking strip on doors false frames.

#### ADVANTAGES

- Adhesive product for easy positioning.
- Suitable in combination with all the flanking strips of the Isolmant range.
- Preformed to size.
- Smart and easy installation.
- Unalterable over time.
- Unlimited duration.

## ISOLMANT TELAIO PORTE TECHNICAL SPECIFICATIONS

NOMINAL THICKNESS:	5 mm
CE MARKING:	Harmonised standards for CE marking are NOT currently available for acoustic insulation products. This means that Isolmant products are currently NOT subject to CE marking, nor to the drawing up of a PDO (declaration of performance) or DDP (declaration of performance). All Isolmant products are placed on the market in compliance with the regulations in force in the country of destination and with the necessary certifications to guarantee their use in dedicated applications.
SIZE:	Base approx. 5 cm / Inside opening approx. 11 cm / Height approx. 10 cm
PACKAGE:	30 pieces box

### ITEM SPECIFICATIONS

Preformed and adhesive polyethylene accessory with dimensions of approx. 11 cm for the internal opening and 10 cm for the height, designed to guarantee the continuity of the perimeter strip in correspondence with the false frames. Nominal thickness 5 mm.

## ISOLMANT TELAIO PORTE INSTALLATION



1

**Installing Isolmant Telaio Porte.** In case of pillars, doors and other movements of the walls, any Fascia Perimetrale flanking strip Isolmant must be shaped without interruption to follow faithfully the perimeter of the premises. In order to make the installation of the aforementioned strip easier, faster and more effective, avoiding cutting and bending operations, in correspondence with the false frames of the doors, we recommend the installation of Isolmant Telaio Porte, already preformed to size and adhesive.

### WARNINGS:

\*This data sheet does not constitute a specification and, if it consists of several pages, please ensure that you have consulted the complete document. Although these instructions are the result of our best expertise they are indicative. The user should establish whether the product is suitable for its intended application. The user will be also in charge of all the responsibility for the use of the product itself.

\*\*The sound insulation values given in this technical data sheet are the result of laboratory tests or tests carried out on site: they cannot be considered a predictive value for every situation that may occur on site. Acoustic performance is closely linked to the specific conditions of each site.

\*\*\*Caution: do not expose the product to direct sunlight.

**isolmant**



Via dell'Industria 12, Località Francolino 20074 Carpiano (Mi) Tel. +39 02 9885701 Fax +39 02 98855702  
clienti@isolmant.it - www.isolmant.it - www.sistemapavimento.it - www.isolmant4you.it

Isolmant is a TECNASFALTI srl's registered trademark - © TECNASFALTI - All rights reserved - Copying, even partially, is forbidden - In force since November 2020 - This document supersedes and replaces all previous versions.